



Preparing for the New Era of Laboratories

MATERIAL SAFETY DATA SHEET (MSDS)

According to regulation (EU) no.1907/2006

METHANOL (DRIED) ANHYDROUS 99,8% AR

PRODUCT CODE : B-3049

CAS No : 67-56-1

FORMULA : CH_3OH

UN No : 1230

website : www.labotiq.net

MATERIAL SAFETY DATA SHEET (SDS/MSDS)

METHANOL (DRIED) ANHYDROUS 99,8%



MSDS Number : 0224

Date : March 21, 2025

Version : 1.0

SECTION 1: Identification of the substance/mixture and of the company/undertaking

- 1.1 Product Name** : METHANOL (DRIED) ANHYDROUS 99,8%
Synonyms : Methyl alcohol; Wood alcohol; Methylol; Wood Spirit, Carbinol, Hydroxymethane, MeOH.
CAS No. : 67-56-1
HS Code : 2905 11 00
Chemical Formula : CH₃OH CH₄O Hill
Molecular Weight : 32.04 g/mol
Product Code : B-3049
Brand : Labotiq
1.2 Manufacturer : Labotiq
Address : Jl.Terapi Raya AD2-Bumi Menteng Asri Bogor, Jawa Barat Indonesia – 16111
Website : www.labotiq.net
Email : labotiq.id@gmail.com,
For information : Phone : (+62-251) 839110, 8311662, Fax : (+62-251) 83135710
Emergency number : +6281316894650
1.3 Application : Laboratory chemicals, Manufacture of substances, General Chemical reagent

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) No 1272/2008

Flammable liquids (Category 2), H225
 Acute toxicity, Oral (Category 3), H301
 Acute toxicity, Inhalation (Category 3), H331
 Acute toxicity, Dermal (Category 3), H311
 Specific target organ toxicity - single exposure (Category 1), Eyes, H370

For the full text of the H-Statements mentioned in this Section, see Section 16

2.2 Label elements

Labelling according Regulation (EC) No 1272/2008

Pictogram



Signal word

Danger

Hazard statement(s)

H225
 H301 + H311 + H331
 H370

Highly flammable liquid and vapour.
 Toxic if swallowed, in contact with skin or if inhaled.
 Causes damage to organs

Precautionary statement(s)

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P260

Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.

P280

Wear protective gloves/ protective clothing/ eye protection/ face protection.

MATERIAL SAFETY DATA SHEET (SDS/MSDS)

METHANOL (DRIED) ANHYDROUS 99,8%



MSDS Number : 0224

Date : March 21, 2025

Version : 1.0

P301 + P310 + P330 IF SWALLOWED: Immediately call a POISON CENTER/doctor. Rinse mouth.
 P308 + P311 IF exposed or concerned: Call a POISON CENTER/doctor.
 P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
 P403 + P233 Store in a well-ventilated place. Keep container tightly closed.

Supplemental Hazard Statements none

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SECTION 3: Composition/information on ingredients

3.1 Substances

Synonyms : Methyl alcohol; Wood alcohol; Methylol; Wood Spirit, Carbinol, Hydroxymethane, MeOH
 Formula : CH_3OH CH_4O Hill
 Molecular weight : 32.04 g/mol
 CAS-No. : 67-56-1
 EC-No. : 200-659-6
 Index-No. : 603-001-00-X

3.2 Mixture

Hazardous ingredients according to Regulation (EC) No 1272/2008

Component	Classification	Concentration
Methanol CAS-No. 67-56-1 EC-No. 200-659-6 Index-No. 603-001-00-X	Flam. Liq. 2; Acute Tox. 3; STOT SE 1; H225, H301, H331, H311, H370 Concentration limits: $\geq 10\%$: STOT SE 1, H370; 3 - $< 10\%$: STOT SE 2, H371;	$\leq 100\%$

For the full text of the H-Statements mentioned in this Section, see Section 16

SECTION 4: First aid measures

4.1 Description of first aid measures

General advice

Consult a physician. Show this safety data sheet to the doctor in attendance.

If inhaled

If breathed in, move person into fresh air. If not breathing, give artificial respiration. Consult a physician.

In case of skin contact

Wash off with soap and plenty of water. Take victim immediately to hospital. Consult a physician.

In case of eye contact

Flush eyes with water as a precaution.

MATERIAL SAFETY DATA SHEET (SDS/MSDS)

METHANOL (DRIED) ANHYDROUS 99,8%



MSDS Number : 0224

Date : March 21, 2025

Version : 1.0

If swallowed

Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

Notes to physician

Dizziness Drowsiness metabolic acidosis Blurred vision Seizures. Coma Blindness death

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Dry powder Dry sand

Unsuitable extinguishing media

Do NOT use water jet.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

5.4 Further information

Use water spray to cool unopened containers.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Wear respiratory protection. Avoid breathing vapours, mist or gas. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. For personal protection see section 8.

6.2 Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

6.3 Methods and materials for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

6.4 Reference to other sections

For disposal see section 13.

MATERIAL SAFETY DATA SHEET (SDS/MSDS)

METHANOL (DRIED) ANHYDROUS 99,8%



MSDS Number : 0224

Date : March 21, 2025

Version : 1.0

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition.

Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition. Keep locked up or in an area accessible only to qualified or authorized persons.

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Derived No Effect Level (DNEL)

Application Area	Exposure routes	Health effect	Value
Workers	Skin contact	Long-term systemic effects	40mg/kg BW/d
Consumers	Skin contact	Long-term systemic effects	8mg/kg BW/d
Consumers	Ingestion	Long-term systemic effects	8mg/kg BW/d
Workers	Skin contact	Acute systemic effects	40mg/kg BW/d
Consumers	Skin contact	Acute systemic effects	8mg/kg BW/d
Consumers	Ingestion	Acute systemic effects	8mg/kg BW/d
Workers	Inhalation	Acute systemic effects	260 mg/m ³
Workers	Inhalation	Acute local effects	260 mg/m ³
Workers	Inhalation	Long-term systemic effects	260 mg/m ³
Workers	Inhalation	Long-term local effects	260 mg/m ³
Consumers	Inhalation	Acute systemic effects	50 mg/m ³
Consumers	Inhalation	Acute local effects	50 mg/m ³
Consumers	Inhalation	Long-term systemic effects	50 mg/m ³
Consumers	Inhalation	Long-term local effects	50 mg/m ³

MATERIAL SAFETY DATA SHEET (SDS/MSDS)

METHANOL (DRIED) ANHYDROUS 99,8%



MSDS Number : 0224

Date : March 21, 2025

Version : 1.0

Predicted No Effect Concentration (PNEC)

Compartment	Value
Soil	23,5 mg/kg
Marine water	15,4 mg/l
Fresh water	154 mg/l
Fresh water sediment	570,4 mg/kg
Onsite sewage treatment plant	100 mg/kg

8.2 Exposure controls

Appropriat engineering controls

Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product

Personal protective equipment

Eye/face protection

Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection

Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching glove's outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

Full contact

Material: butyl-rubber
Minimum layer thickness: 0,7 mm
Break through time: 480 min
Material tested:Butoject®

Splash contact

Material: Viton®
Minimum layer thickness: 0,7 mm
Break through time: 120 min
Material tested:Vitoject®

Body Protection

Complete suit protecting against chemicals, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure

Prevent further leakage or spillage if safe to do so. Do not let product enter drains

MATERIAL SAFETY DATA SHEET (SDS/MSDS)

METHANOL (DRIED) ANHYDROUS 99,8%



MSDS Number : 0224

Date : March 21, 2025

Version : 1.0

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

Appearance	Form: liquid
	Colour: colourless
Odour	characteristic
Odour Threshold	10 ppm
pH	No data available
Melting point/freezingpoint	Melting point/range: -98 °C
Initial boiling point and boiling range	64,7 °C
Flash point	9,7 °C - closed cup - Regulation (EC) No. 440/2008, Annex, A.9
Evaporation rate	6,3 - Diethyl ether1,9 - n-butyl acetate
Flammability (solid, gas)	No data available
Upper/lower flammability or explosive limits	Upper explosion limit: 44 %(V) Lower explosion limit: 5,5 %(V)
Vapour pressure	No data available
Vapour density	169,27 hPa at 25 °C
Relative density	1,11
Water solubility	0,791 g/mL at 25 °C
Partition coefficient: noctanol/water	1.000 g/l at 20 °C - completely miscible at 20 °C soluble
Auto-ignition temperature	log Pow: -0,77 - (Lit.), Bioaccumulation is not expected.
Decomposition temperature	455,0 °C at 1.013 hPa - DIN 51794
Viscosity	Distillable in an undecomposed state at normal pressure.
	Viscosity, kinematic: 0,54 - 0,59 mm ² /s at 20 °C
	Viscosity, dynamic: > 0,544 - < 0,59 mPa.s at 25 °C
Explosive properties	No data available
Oxidizing properties	No data available

9.2 Other safety information

Minimum ignition energy	0,14 mJ
Conductivity	< 1 µS/cm
Relative vapour density	1,11

SECTION 10: Stability and reactivity

10.1 Reactivity

No data available

10.2 Chemical stability

Stable under recommended storage conditions.

10.3 Possibility of hazardous reactions

Risk of explosion with: Oxidizing agents perchloric acid perchlorates salts of oxyhalogenic acids chromium(VI) oxide halogen oxides nitrogen oxides nonmetallic oxides chromosulfuric acid chlorates hydrides zinc diethyl halogens powdered magnesium hydrogen peroxide Nitric acid sulfuric acid permanganic acid sodium hypochlorite

Exothermic reaction with: acid halides Acid anhydrides Reducing agents acids Bromine Chlorine Chloroform magnesium tetrachloromethane

MATERIAL SAFETY DATA SHEET (SDS/MSDS)

METHANOL (DRIED) ANHYDROUS 99,8%



MSDS Number : 0224

Date : March 21, 2025

Version : 1.0

Risk of ignition or formation of inflammable gases or vapours with: Fluorine Oxides of phosphorus
Raney-nickel Generates dangerous gases or fumes in contact with: Alkaline earth metals Alkali metals

10.4 Conditions to avoid

Heat, flames and sparks.

10.5 Incompatible materials

various plastics, magnesium, zinc alloys

10.6 Hazardous decomposition products

In the event of fire: see section 5

MATERIAL SAFETY DATA SHEET (SDS/MSDS)

METHANOL (DRIED) ANHYDROUS 99,8%



MSDS Number : 0224

Date : March 21, 2025

Version : 1.0

SECTION 11: Toxicological information

11.1 Information on toxicological effects**Acute toxicity**

Acute toxicity estimate Oral - 100,1 mg/kg (Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Symptoms: Nausea,

Vomiting Acute toxicity estimate Inhalation - 4 h - 3,1 mg/l (Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Symptoms: Irritation symptoms in the respiratory tract.

Acute toxicity estimate Dermal - 300,1 mg/kg (Expert judgment)

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Skin corrosion/irritation

Skin - Rabbit

Result: No skin irritation

Remarks: (ECHA) Drying-out effect resulting in rough and chapped skin.

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation

Remarks: (ECHA)

Respiratory or skin sensitisation

Sensitisation test: - Guinea pig

Result: negative (OECD Test Guideline 406)

Germ cell mutagenicity

Based on available data the classification criteria are not met. Test Type: Ames test

Test system: Salmonella typhimurium

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative Test Type: In vitro mammalian cell gene mutation test

Test system: Chinese hamster lung cells

MATERIAL SAFETY DATA SHEET (SDS/MSDS)
METHANOL (DRIED) ANHYDROUS 99,8%

MSDS Number : 0224

Date : March 21, 2025

Version : 1.0

Metabolic activation: with and without metabolic activation
Method: OECD Test Guideline 476
Result: negative
Test Type: Micronucleus test Species: Mouse Cell type: Bone marrow
Application Route: Intraperitoneal injection
Method: OECD Test Guideline 474
Result: negative

Carcinogenicity

Did not show carcinogenic effects in animal experiments.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

Reproductive toxicity

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

Causes damage to organs. - Eyes, Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No aspiration toxicity classification

Additional Information

RTECS: PC1400000

Acute effects:, Headache, Dizziness, Drowsiness, narcosis, Blindness, Impairment of vision, irritant effects, Nausea, Vomiting, agitation, spasms, inebriation, Coma
Drying-out effect resulting in rough and chapped skin.

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Systemic effects: acidosis drop in blood pressure

agitation, spasms inebriation Dizziness Drowsiness Headache Impairment of vision Blindness narcosis Coma Symptoms may be delayed. Damage to: Liver Kidney Cardiac Irreversible damage of the optical nerve. Other dangerous properties can not be excluded. This substance should be handled with particular care.

SECTION 12: Ecological information**12.1 Toxicity**

Toxicity to fish

flow-through test LC50 - *Lepomis macrochirus* (Bluegill) - 15.400,0 mg/l - 96 h (US-EPA)

Toxicity to daphnia and other aquatic invertebrates

semi-static test EC50 - *Daphnia magna* (Water flea) - 18.260 mg/l - 96 h
(OECD Test Guideline 202)

Toxicity to algae

static test ErC50 - *Pseudokirchneriella subcapitata* (green algae) - ca. 22.000,0 mg/l - 96 h
(OECD Test Guideline 201)

MATERIAL SAFETY DATA SHEET (SDS/MSDS)

METHANOL (DRIED) ANHYDROUS 99,8%



MSDS Number : 0224

Date : March 21, 2025

Version : 1.0

Toxicity to bacteria static test IC50 - activated sludge - > 1.000 mg/l - 3 h
(OECD Test Guideline 209)

12.2 Persistence and degradability

Biodegradability

Result: 99 % - Readily biodegradable. (OECD Test Guideline 301D)

Biochemical Oxygen Demand (BOD) 600 - 1.120 mg/g

Remarks: (IUCLID)

Chemical Oxygen Demand (COD) 1.420 mg/g

Remarks: (IUCLID)

Theoretical oxygen demand 1.500 mg/g

Remarks: (Lit.) Ratio BOD/ThBOD 76 %

Remarks: Closed Bottle test(IUCLID)

12.3 Bioaccumulative potential

Bioaccumulation Cyprinus carpio (Carp) - 72 d at 20 °C - 5 mg/l(Methanol)

Bioconcentration factor (BCF): 1,0

12.4 Mobility in soil

Will not adsorb on soil

12.5 Results of PBT and vPvB assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Additional ecological information Avoid release to the environment.

Stability in water at 19 °C 83 - 91 % - 72 h Remarks: Hydrolyzes on contact with water. Hydrolyzes readily.

SECTION 13: Disposal considerations

13.1 Waste treatment methods

Product

Offer surplus and non-recyclable solutions to a licensed disposal company. Waste material must be disposed of in accordance with the Directive on waste 2008/98/EC as well as other national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

Contaminated packaging

Dispose of as unused product.

SECTION 14: Transport information

14.1 UN number

ADR/RID: 1230

IMDG: 1230

IATA: 1230

14.2 UN proper shipping name

ADR/RID: METHANOL

IMDG: METHANOL

IATA: Methanol

14.3 Transport hazard class(es)

ADR/RID: 3 (6.1)

IMDG: 3 (6.1)

IATA: 3 (6.1)

MATERIAL SAFETY DATA SHEET (SDS/MSDS)
METHANOL (DRIED) ANHYDROUS 99,8%

MSDS Number : 0224

Date : March 21, 2025

Version : 1.0

14.4 Packaging group

ADR/RID: II

IMDG: II

IATA: II

14.5 Environmental hazards

ADR/RID: no

IMDG Marine pollutant: no

IATA: no

14.6 Special precautions for user

No data available

SECTION 15: Regulatory information**15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

This safety datasheet complies with the requirements of Regulation (EC) No. 1907/2006.

15.2 Chemical safety assessment

For this product a chemical safety assessment was not carried out

SECTION 16: Other information**Full text of H-Statements referred to under sections 2 and 3.**

H225	Highly flammable liquid and vapour.
H301	Toxic if swallowed.
H301 + H311 + H331	Toxic if swallowed, in contact with skin or if inhaled.
H311	Toxic in contact with skin.
H331	Toxic if inhaled.
H370	Causes damage to organs
H371	May cause damage to organs.

National Fire Protection Association (U.S.A.):

Health: 1

Flammability: 3

Reactivity: 0

Further information

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. Labotiq shall not be held liable for any damage resulting from handling or from contact with the above product.

Version : 1.0

Revision Date : August 26, 2024